

Compact Print & Apply

The Industry's economical print & apply solution

Mountable to all cardboard production lines

Efficient labelling

Extremely stable construction

All materials made of stainless and anodised aluminium



With its compact design, the HM compact fulfills all industry requirements for dependability, handling and performance.

It can apply labels to the top and sides of products and features a Datamax M-Class 203 or 300dpi printer.



Technical Specification

Maximum label speed	15m/min
Printer	Direct thermal printer
Print resolution	203/300dpi
Max print speed	204mm/sec, 156mm/sec
Print width	50-118mm
Print length	50-118mm
Max. label roll diameter	203mm
Applicator	
Cylinder length	250mm (60mm effective length)
Vacuum foot size	100x100mm (max label 118x118mm)
Applied label sensor	Yes
Controls	Internal microprocessor standard 24V DC with potential for free alarm and application-start switches
Weight	17-20kg
Dimensions H X W X L	262 and 500mm at the cylinder x 300mm x 550mm

Options

- Thermal transfer (film)
- Printer 203 dpi 254mm/sec - Printer with display
- Printer 300 dpi print resolution with display
- Network card DMX 10/100m/Bit LAN
- External alarm light
- Extra long cylinder 350mm (60 effective length)
- H-foot
- Spindle for up/down adjustment
- Mounting for top labelling and side labelling
- Product photocell