

High end, high speed inline printer

Mountable to all cardboard production lines

Efficient labelling

Extremely stable construction

All materials made of stainless and anodised aluminium

The HM Pro A mounts on all well-known dispensers, e.g. HM 3000 and HM 4000 CW.

The construction is very stable made of stainless steel and anodised aluminium, with a high capacity it guarantees an efficient labelling.

With an optional ribbon optimization the consumption of thermal transfer ribbon can be reduced.

Technical Specification

Resolution	203 or 300 dpi
Print speed	50-304mm/sec
Feed rate	50-304mm/sec
Print (w x l)	104mm x 6-2500mm
Label (w x l)	25-118mm x 19-1000mm
Ribbon (w x l)	25-118mm x 600mm
Technology	Direct thermal transfer
Drive motor	Stepper motor
Versions	Left and right hand
Display	LCD graphic display with backlight
Electronics	Microprocessor
IP protection	Dispenser IP32, panel IP65
Dimensions	270 x 215 x 230.5mm



Options

- **EXTERNAL OPERATION** – user-friendly panel in RF steel box can be mounted anywhere on the line
- **NETWORK** – optional connection to HM LabNet via Ethernet ensures central operation and control
- **INTELLIGENCE** – optional active, communicating unit that can receive/send real time data